


Glide plug / End plug for oval tube

IB-IPO1

Foot and end plug with flanges. Available in several colours and sizes. Suitable for tubes and deeper holes where sharp edges and shape variations may occur.

Note: *Not suitable for holes in sheet metal etc.*



Art. no	A1	A2	B1	B2	D1	D2	M1
IPO10201-2G	20	10	16-18	6-8	3	11	PE-LD
IPO10201-2S	20	10	16-18	6-8	3	11	PE-LD
IPO15301-2S	30	15	26-28	11-13	3	15	PE-LD
IPO15301-2V	30	15	26-28	11-13	3	15	PE-LD
IPO16361-2G	36	16	32-34	12-14	6	13	PE-LLD
IPO16361-2S	36	16	32-34	12-14	6	13	PE-LLD
IPO16361-2V	36	16	32-34	12-14	6	13	PE-LLD
IPO20351-2S	35	20	31-33	16-18	5.5	11.5	PE-LD
IPO20351-2V	35	20	31-33	16-18	5.5	11.5	PE-LD
IPO20401-2G	40	20	36-38	16-18	5	15	PE-LLD
IPO20401-2S	40	20	36-38	16-18	5	15	PE-LLD
IPO20401-2V	40	20	36-38	16-18	5	15	PE-LLD
IPO20501-2G	50	20	46-48	16-18	5	11.5	PE-LD
IPO20501-2S	50	20	46-48	16-18	5	11.5	PE-LD

Address Ackurat Industriplast AB
Värnamovägen 42
360 30 Lammhult
Sweden

Phone +46 (0)472 26 93 00
E-mail info@ackurat.se
Web ackurat.com

Art. no	A1	A2	B1	B2	D1	D2	M1
IPO20501-2V	50	20	46-48	16-18	5	11.5	PE-LD
IPO20601-2S	60	20	56-58	16-18	5	13.5	PE-LD
IPO25501-3S	50	25	44-48	19-23	5	12	PE-LD
IPO258012-25S	80	25	75-77.6	20-22.6	5	14.5	PE-LD
IPO30501-3G	50	30	44-48	24-28	5	11.5	PE-LD
IPO30501-3S	50	30	44-48	24-28	5	11.5	PE-LD
IPO30601-2G	60	30	56-58	26-28	4.5	13.5	PE-LD
IPO30601-2S	60	30	56-58	26-28	4.5	13.5	PE-LD

Gray RAL 7001 *Black RAL 9005* *White RAL 9010* *Gray NCS:S 3502-B* *Black RAL 9017*
WHITE RAL 9016

Address Ackurat Industriplast AB
Värnamovägen 42
360 30 Lammhult
Sweden

Phone +46 (0)472 26 93 00
E-mail info@ackurat.se
Web ackurat.com