




Fotplugg / Ändplugg för ovalt rör – rundad

IB-IPO2

Utan flänsar.

Notera: Mindre lämpliga för hål där skarpa kanter och formvariationer kan förekomma.



Art. nr	A1	A2	B1	B2	D1	D2	M1
IPO12251.5G	25	12	22	9	2	12	★ PE-LLD
IPO12251.5S	25	12	22	9	2	12	◆ PE-LLD
IPO12251.5V	25	12	22	9	2	12	☆ PE-LLD
IPO12321.5G	32	12	29	9	3	10	★ PE-LLD
IPO12321.5S	32	12	29	9	3	10	◆ PE-LLD
IPO12321.5V	32	12	29	9	3	10	☆ PE-LLD
IPO12321G	32	12	30	10	3	10	★ PE-LLD
IPO12321S	32	12	30	10	3	10	◆ PE-LLD
IPO12321V	32	12	30	10	3	10	☆ PE-LLD
IPO25451.5G	45	25	42	22	3	12	★ PE-LLD
IPO25451.5S	45	25	42	22	3	12	◆ PE-LLD
IPO25451.5V	45	25	42	22	3	12	☆ PE-LLD
IPO25602G	60	25	56	21	5	25	★ PE-LLD
IPO25602S	60	25	56	21	5	25	◆ PE-LLD

Art. nr	A1	A2	B1	B2	D1	D2	M1
IPO25602V	60	25	56	21	5	25	☆ PE-LLD

★ *Grå NCS:S 3502-B*
 ◆ *Svart RAL 9017*
 ☆ *VIT RAL 9016*