




Wing-handle indexing plunger with two positions - steel

LCNS-001

To be mounted in a threaded hole. Hardened pin. Nut included. With two positions.



Art. no	A	B	C	D1	D2	D3	M1
LCNS001514	25	M10X1	4	12	20	6	▲ Steel
LCNS001515	25	M10X1	5	12	20	6	▲ Steel
LCNS001516	25	M10X1	6	12	20	6	▲ Steel
LCNS00154	25	M10	4	12	20	6	▲ Steel
LCNS00155	25	M10	5	12	20	6	▲ Steel
LCNS00156	25	M10	6	12	20	6	▲ Steel
LCNS00161.55	30	M12X1.5	5	13.8	25	8	▲ Steel
LCNS00161.56	30	M12X1.5	6	13.8	25	8	▲ Steel
LCNS00161.58	30	M12X1.5	8	13.8	25	8	▲ Steel
LCNS00165	30	M12	5	13.8	25	8	▲ Steel
LCNS00166	30	M12	6	13.8	25	8	▲ Steel
LCNS00168	30	M12	8	13.8	25	8	▲ Steel
LCNS00171.510	40	M16X1.5	10	18.4	32	10	▲ Steel
LCNS00171.56	40	M16X1.5	6	18.4	32	10	▲ Steel

Art. no	A	B	C	D1	D2	D3	M1
LCNS00171.58	40	M16X1.5	8	18.4	32	10	▲ Steel
LCNS001710	40	M16	10	18.4	32	10	▲ Steel
LCNS00176	40	M16	6	18.4	32	10	▲ Steel
LCNS00178	40	M16	8	18.4	32	10	▲ Steel
LCNS00181.510	50	M20X1.5	10	23	35	12	▲ Steel
LCNS00181.512	50	M20X1.5	12	23	35	12	▲ Steel
LCNS00181.58	50	M20X1.5	8	23	35	12	▲ Steel
LCNS001810	50	M20	10	23	35	12	▲ Steel
LCNS001812	50	M20	12	23	35	12	▲ Steel
LCNS00188	50	M20	8	23	35	12	▲ Steel

▲ Black