




Steel/stainless spring pressure screw – hex socket

PSTS-008

Screw with spring loaded ball (Plunger). Suitable when adjustment is needed. Stainless steel. Hex socket (Allen).

Note: C = Maximum pressure 'N' (approximate).



Art. no	A	B	C	D1	D2	M1	M2
PSTS008093	M3	1.5	3	9	0.5	Stainless steel A2	Stainless steel A2
PSTS008097	M3	1.5	7	9	0.5	Stainless steel A2	Stainless steel A2
PSTS00811010	M4	2.5	10	10	0.8	Stainless steel A2	Stainless steel A2
PSTS00811022	M4	2.5	22	10	0.8	Stainless steel A2	Stainless steel A2
PSTS00811610	M4	2.5	10	16	0.8	Stainless steel A2	Stainless steel A2
PSTS00821411	M5	3	11	14	0.9	Stainless steel A2	Stainless steel A2
PSTS00821430	M5	3	30	14	0.9	Stainless steel A2	Stainless steel A2
PSTS00822011	M5	3	11	20	0.9	Stainless steel A2	Stainless steel A2
PSTS00831540	M3	1.5	3	9	0.5	Steel	Steel
PSTS00832513	M6	3.5	13	25	1	Stainless steel A2	Stainless steel A2
PSTS00841830	M4	2.5	10	10	0.8	Steel	Steel
PSTS00841873	M8	5	73	18	1.5	Stainless steel A2	Stainless steel A2
PSTS00843030	M8	5	30	30	1.5	Stainless steel A2	Stainless steel A2
PSTS008523100	M10	6	100	23	2	Stainless steel A2	Stainless steel A2

Art. no	A	B	C	D1	D2	M1	M2
PSTS00852335	M10	6	35	23	2	 Stainless steel A2	 Stainless steel A2
PSTS00853535	M10	6	35	35	2	 Stainless steel A2	 Stainless steel A2
PSTS008626120	M12	8	120	26	2.5	 Stainless steel A2	 Stainless steel A2
PSTS00862655	M12	8	55	26	2.5	 Stainless steel A2	 Stainless steel A2
PSTS00864055	M12	8	55	40	2.5	 Stainless steel A2	 Stainless steel A2

 *Steel (stainless)*